



Superfine sander with linear (not rotary) sanding motion.



Pensander PS 13

This superfine sander with linear sanding motion (versus rotary or orbital) operates at 8,000 strokes per minute with a 3/32" (2.5mm) stroke. It is ideal for surfaces, slots and tight corners. Included are four sanding attachments with straight shanks and 4 with angled shanks (four different shapes per shank style) as well as 3 sheets of preprofiled adhesive sanding pads. The sheets are 180, 240 and 400 grit with 5 of each shape per sheet.





Technical data:

Direct voltage 12 - 18V

Speed 8,000 strokes per minute

with 3/32" (2.5mm)

Length 6.3" (160mm) Weight 0.29 lb (130g)

Note:

An AC adapter of at least 12 - 18V DC and 1.0A is required. We recommend PROXXON power supplies **NG 2/S** or **NG 5/E**. The electronic speed control on the NG 5/E unit allows the selection of different speeds for different applications and materials.

NO 28 594



1

California Residents Prop 65 Information



MARNING:

This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.





Replacement Sandpaper for the PS 13

Three sheets, each with 20 pads (5 each of the four shapes, adhesive).

NO 28 822 180 grit NO 28 824 240 grit NO 28 826 400 grit