



MICROMOT AC voltage adapters - safe and efficient power sources for hand held 12 volt machines.



MICROMOT AC Adapter NG 2/S

Very compact design. Noryl casing is heat resistant - a necessity for transformer enclosures. Capacity 2,0A at 16 Volt open circuit - and 12 Volt under load = 24VA (DC). Primary supply 110 - 120V. Polarized socket for MICROMOT plug. Red LED indicates

readiness for use. PTC (Positive temperature coefficient) element prevents overload, plugged in tool will not automatically restart. After cooling down, the AC wall plug should be disconnected briefly to reset the adapter. Modern design with holes for storing bits. Foldable tool rest provides a secure place for keeping the MICROMOT tool ready for use.

Tool and accessories not included.

NO 38 706



See us on YouTube!

California Residents Prop 65 Information

⚠ WARNING:

This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

This transformer is the optimal power source for these fine PROXXON tools:

Rotary Tool MICROMOT 60

Rotary Tool MICROMOT 60/E

Rotary Tool MICROMOT 60/EF

Pensander PS 13

Jig Saw STS 12/E

Engraver GG 12

Precision Drill Grinder FBS 12/EF

Note:

Power consumption of portable machine tools is measured according to the internationally accepted ICE-745-1 specification. The current drawn is measured, not the power consumption with a hot motor just before stalling. In practice, this condition seldom appears, if ever. All PROXXON AC adapters are suitably dimensioned for the recommended purposes.