



A precision device for fine sanding work and minor material correction. Variable speed 1150 - 3600 rpm.

Disc Sander TG 125/E



- Suction channel with adapter to connect a vacuum cleaner.
- 😢 5"(125 mm) sanding disc. Adhesive sanding discs can be easily removed after use.
- 10 Table can be adjusted to incline 50° downward and 10° upward. With miter gage and c-clamp for horizontal and vertical clamping.

For all types of wood, steel, non-ferrous and precious metals, plastics (also Plexiglas and fiber glass).

Powerful, vibration-free running due to a powerful and balanced DC motor. Housing made of fiber glass reinforced POLYAMID. Aluminum table, adjustable to incline 50° downward and 10° upward; with miter gage. Sanding disc with affixed silicon film. This surface ensures easy removal of self-adhesive sandpaper. Two additional square silicon sheets ensure that used discs can be stored and reused as necessary. Can be mounted horizontally and vertically to a table or workbench with the included c-clamp.

Also includes an adapter to attach a vacuum cleaner for dust free working, as well as 2 each sanding discs 80, 150 and 240 grit.

Technical data:

Speed 1150 - 3600rpm (250 - 800m/min)

Disc Diameter 5" (125mm) sanding disc

Max. Sanding Height off the table 2.46" (62.5mm)

Table Size 3.9" x 5.5" (98 x 140mm)

Sanding height Size 11.8" x 5.5" x 6.3" (300 x 140 x 160mm)

Volts 110 V. 140W. 50/60 Hz

Weight approx. 6.6 lbs (3kg)

NO 37 060



California Residents Prop 65 Information



M WARNING:

This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Adhesive Sanding Discs for TG 125/E

Industrial quality. For sanding of soft and hard wood, chip boards, fiber boards, non ferrous metals, steel, plastics, cork, rubber and minerals. Diameter 5" (125 mm). One square silicon sheet for storage and reuse of used sanding discs is included.

NO 28 160 80 grit 5 pieces NO 28 162 150 grit 5 pieces 240 grit NO 28 164 5 pieces







Comes with c-clamp to quickly and securely fasten sander to workbench either vertically or horizontally.